



SINOBOOM 星邦重工

GTJZ1212

- Imported battery offers 8 hours run time under normal conditions
- Highly stable - can operate on 3 degree longitudinal and 1.5 degree lateral slope
- Super low maintenance self-lubricating bearings in some components
- Platform can be dismantled for transportation



I. Technical Parameters

Technical Parameters

Model	GTJZ1212
Productivity	
Max. Platform height	11.9M
Max. Working height	13.9M
Extension outreach	0.9M
Turning radius (outside)	2.35M
Turning radius (inside)	0M
Rising/Falling speed (Without loading)	63~68s/44~49s
Grade ability	25%
Load capacity (Platform)	320kg
Driving Speed(stowed)	0~3.2km/h
Driving Speed (raised)	0~0.8km/h
Max allowable wind speed	12.5m/s
Max allowable slope (front/back)	3°
Max allowable slope (side/side)	1.5°
Max. Platform Occupants(Indoor)	2
Max. Platform Occupants(Outdoor)	1
Max. Allowable Side Force(Indoor)	400N
Max. Allowable Side Force(Outdoor)	200N
Dimensions	
Overall length(stowed)	2.39M
Overall width(stowed)	1.15M
Overall height (stowed, Guardrail folded)	1.98M
Overall height (stowed, Guardrail unfolded)	2.6M
Ground clearance	0.1M
Wheelbase	1.85M
Platform Size (L*W*H)	2.25*1.15*1.1M
Overall weight(for indoor and outdoor use)	2900kg
Overall weight(indoor use only)	2615kg
Tire	380*125 MM/solid
Hydraulic oil tank vol.	35L
Battery	6V*4/260AH
Control Voltage	24VDC

II.Product Configurations

Standard Configurations

NO.	Items	Producer
1	Driving Motor	WHITE from USA
2	Brake	WHITE from USA
3	Hydraulic Valve	HydraForce from USA
4	Electric Motor	CHINA
5	Gear Pump	CHINA
6	Hydraulic hose	EATON from USA
7	Scissor assembly	SINOBOOM
8	Work Platform	SINOBOOM
9	Under frame	SINOBOOM
10	Paint	SINOBOOM
11	Electric Controller	Curtis from USA
12	Charger	CHINA
13	Pressure Sensor	Honelly from USA
14	Angel Sensor	Honelly from USA
15	Level Switch	PARKER from USA
16	Controller	Deltatech from USA
17	Battery	Trojan from USA
18	AC power outlets	CHINA
19	flashing warning lights	CHINA
20	Chassis conduction band	CHINA

Optional configurations and devices:

1. 260Ah batteries of Trojan;
2. Charging cable apply to socket standards from different countries.

Remark: For the items which will cost extra, please refer to the commercial quotation related.

III. Contact us

HUNAN SINOBOOM HEAVY INDUSTRY CO.,LTD

Add: NO. 128, East Jinzhou Avenue, Ningxiang High-tech industrial park, Changsha, Hunan, China.

E-Mail: Sales@sinoboom.com

Tel: +86-731-87116222

Website: <http://www.sinoboom.com>